




Product type: Straight Bulkhead Cable Jacks

Product number: GLB13BNC

| | | |
|---------------------------------|--|--------|
| Frequency Range(GHz) | 3 | |
| Characteristic impedance(ohm) | 50 | |
| VSWR | ≤1.30 | |
| Insulation resistance | ≥5000MΩ | |
| Dielectric Withstanding voltage | 1500V(rms) | |
| Disengage force | ≥0.6N | |
| Contact resistance | Center conductor | ≤1.5mΩ |
| | Outer conductor | ≤1mΩ |
| Connector | BNC | |
| Apply cable | 4/50S | |
| Length(mm) | Φ 14.5*34*4.2(Φ A=4.2) | |
| Durability | 500 Cycles | |
| MATERIAL AND PLATING | | |
| Lighting protection | DC grounding | |
| Body | Brass,nickel plated | |
| Male center contacts | Brass,gold plated | |
| Female center contacts | Beryllium copper or phosphor bronze ,gold plated | |
| Insulators | PTFE | |
| Crimp ferrules | copper alloy,nickel plated | |
| Temperature range | -65~+165℃ | |



Add: Room 826, Block B,BLDG 18, University Science Park(East), Zhengzhou City,P.R.Henan,China.
 Tel: 86-371-60911368 Email:info@global-antenna.com
 Web:<http://www.asialeren.com> <http://www.global-antenna.com>